

TECHNICAL SPECIFICATION FORM OF THE PRODUCT (ANNEX-4)

History		Sequence No.						136
OKAS CODE	39	1	1	3	4	0	0	
DMO CATALOG CODE NO								
NAME OF THE PRODUCT	Guest couch							
ORIGINAL PRODUCT CODE (P/N)	LUCCA 300 C							
PRODUCT BRAND / MODEL	Goldsit/LUCCA							



TECHNICAL SPECIFICATIONS

GUEST COUCH

Foot Structure	U GUEST FOOT INTEGRATED WITH ARM
Width (mm)	570
Depth (mm)	650
Height (mm)	1000
Backrest Upholstery Material	FAUX LEATHER / FABRIC
Foot Material	METAL PROFILE
Armrest Material	BLACK POLYPROPYLENE
Other Features	20*40*3 MM OVAL PIPE MATERIAL IS USED ON THE FEET.
For Technical Drawing/Drawing	
Company official name signature and stamp	

DESCRIPTIONS

Annex-4 Technical Specification Forms for the Product shall be filled in accordance with the "General Rules" in the "List of Material Types to be Taken into the Catalogue" in the Annexes of the Catalog Announcement.



LUCCA 300 C GUEST CHAIR




ön görünüş



yan görünüş



üst görünüş



arka görünüş

Seating Depth	: 460mm
Seating Surface Width	: 470mm
Height of Back Upper Edge from Seating Surface	: 560mm
Back Width	: 450mm
Width	: 570mm
Depth	: 650mm
Height	: 1000mm

BACKBOARD min. ON 11+6 mm FORMED BEEK PLYWOOD Min. 45 Kg/m³ BULK SPONGE IS USED.

Ø 20x40x3 MM OVAL PIPE AND THE CONSTRUCTION CONSTITUTING THE FOOT AND ARM, IS USED IN THE MIN. 4 mm SHEET BODY CARRIER. CHROME PLATED. PLASTIC SHOES ARE USED TO PREVENT CONTACT WITH THE FLOOR.

Fabric at least 90% Polyester, at least 210 gr/m² / Artificial leather at least 10% polyurethane, 70% PVC, at least 315 gr/m²/File 350 gr/m²

MADE SPECIALLY TO THE MODEL, IN ALUMINUM MOLDS WITH PNC CONTROLLED HIGH PRESSURE MACHINES Min. 45 Kg/m³ BULK FOAM WITHOUT METAL CONSTRUCTION IS USED.

SEAT BOARD min. ON 11 mm FORMED BEEK PLYWOOD Min. 45 Kg/m³ BULK SPONGE IS USED.

FIXED ARM WITH NO UP-DOWN MOVEMENT WITH PLASTIC UPHOLSTERY PAD.