


TECHNICAL SPECIFICATION FORM OF THE PRODUCT (ANNEX-4)


History		Sequence No.					283
OKAS CODE	39	1	1	3	4	0	0
DMO CATALOG CODE NO							
NAME OF THE PRODUCT	Study Chair						
ORIGINAL PRODUCT CODE (P/N)	PAROX 100 PA						
PRODUCT BRAND / MODEL	Goldsit/PAROX						
							
TECHNICAL SPECIFICATIONS							
STUDY CHAIR							
Foot Structure	STAR FOOT						
Width (mm)	620						
Depth (mm)	670						
Height (mm)	1030						
Backrest Upholstery Material	NET FABRIC						
Foot Material	BLACK POLYPROPYLENE						
Armrest Material	BLACK POLYPROPYLENE						
Other Features	P6 30% FIBER GLASS MATERIAL AND SILENT HARD FLOOR WHEEL IS USED ON PLASTIC FEET.						
For Technical Drawing/Drawing							
Company official name signature and							
DESCRIPTIONS							
Annex-4 Technical Specification Forms for the Product shall be filled in accordance with the "General Rules" in the "List of							




PAROX 100 PA WORK CHAIR




ön görünüş



yan görünüş



üst görünüş



arka görünüş

Seating Depth	: 410mm
Seating Surface Width	: 480mm
Height of Back Upper Edge from Seating Surface	: 580mm
Back Width	: 490mm
Star Foot Diameter	: 700mm
Width	: 620mm
Depth	: 670mm
Height	: 1030mm

THE BACK IS PLASTIC AND WITH MESH. IT HAS PLASTIC FIXED WAIST SUPPORT.

SINGLE VISIONARY MERCEDES-BENZ AQUARIC GRINDING, CAN LOCK IN AT LEAST 3 POSITIONS WITH THE HELP OF ARM AND BUTTON AND SINGLE VISUAL VISUAL MERCURIZATION AYAZATIC MECHANISM.

FIVE STAR FORM NYLON 6 30% GLASS FIBER SHOCK ABSORBER HUB WITH ZAMAK BRACE SUPPORTED 1,600 Kg \pm 50 g OCTOPUS FOOT.WHEELS ϕ 11 mm WITH SECOND PIN, 50mm ϕ DUBLE DUBLERE DUPLATILE MALLERZE.

METAL PARTS ARE ELECTROSTATIC PAINTED AND min. IT IS 40 microns thick.

Fabric at least 90% Polyester, at least 210 gr/m² / Artificial leather at least 10% polyurethane, 70% PVC, at least 315 gr/m²/File 350 gr/m²

PP COPOLIMER PLASTIC MATERIAL, HEIGHT ADJUSTABLE, ARMRESTS WITH POLYURETHANE MATERIAL (INTERIOR WITH PLASTIC FRAME).

HIGH PRESSURE MACHINES WITH PLC CONTROL IN ALUMINUM MOLDS MADE SPECIALLY TO THE MODEL Min. 45 Kg/m³ BULK FOAM WITHOUT METAL CONSTRUCTION IS USED.

SEAT MIN. IT CONSISTS OF BEEKEN PAPER FORM FORM WITH 11 mm THICKNESS. THE BOTTOM OF THE SEAT HAS A PP MATERIAL PLASTIC COVER.

IMPORTED CLASS 4 SHOCK ABSORBER IS USED THAT CAN TURN IN 360° ON ITS AXIS.