

KIMERA / KIMERA RELAX



Executive and waiting armchair

Versions:



* SMOOTH VERSION (no stitching)



* RHOMBOIDHAL STITCHING

- **Executive swivel armchair:** with 5-star base on castors or feet, seat height adjustment, with fixed plate or tilting mechanism
- **Relax armchair:** with
 - 4-star chromed fixed or swivel base
 - round chromed fixed or swivel base in stainless steel Ø 580

Back and seat: monocoque shell in steel with filler in expanded cold injected fireproof polyurethane density

min. 60 Kg/m³ with extra cushion for the seat, density 40 PCM

Seat height adjustment: by gas-spring, cone Ø 28 mm.

Actions:

Fixed plate: (for version without mechanism) in black painted steel, thickness 2,5 mm., cone Ø 28 mm.

Only by request: Gas system with automatic return of the chair only for 5-star bases with glides and AL4 base without mechanism.

Tilting mechanism: structure in steel and aluminum with one-lever adjustment for:

- seat height adjustment and tilting movement control (lockable in 5 positions with anti-shock system)
- knob for tension adjustment .



“Knee-tilt” tilting mechanism: steel frame on decentralized axle, with the following adjustments:

- lever for seat height adjustment
- Lever tilt movement control 5 positions
- Back antishock system
- Tension adjustment



Swivel bases and castors:



APN 5 star base with steel inner frame 25x30 mm th.2 mm Ø 670 mm, cover in black polypropylene. (Ansi-Bifma X5.1-1993/8)



AL7 5-star base in die-cast polished aluminum Ø 650 mm



for **APN** and **AL7**: self-braking soft castors Ø 50 mm



APS 5-star base in black reinforced nylon Ø 660 mm



AL6 5-star base in die-cast polished aluminum Ø 654 mm.



for **APS, APG, APW, AL6, ANN** and **AL9**: self-braking soft castors Ø 65 mm



APG 5-star base in grey nylon Ø 675 mm



APW 5-star base in white nylon Ø 675 mm



AL9 5-star base in die-cast aluminum, aluminium grey painted Ø 650 mm



ANN 5-star base in die cast aluminium black painted Ø 654 mm



AL3 5-star base in die-cast polished aluminum Ø 654 mm with chromed gaslift



AL5 5-star base in die-cast polished aluminum Ø 654 mm with chromed gaslift



for **AL3** and **AL5** self-braking soft castors Ø 65 mm **CHROMED**



AWW 5 star base in die cast aluminium white painted Ø 654 mm, with **WHITE GASLIFT**.



for **AWW**: self-braking soft castors Ø 65 mm **WHITE**



AL4 (not for tilting versions) 4-star base in die-cast aluminum Ø 730 mm. with chromed feet and chromed gas-lift



APP 5 star black nylon base Ø 680 with dynamic DUO glides nylon/wool felt

For relax versions – Waiting Area:



**Swivel or fixed
steel base
chromed or
black painted**

4-star fixed or swivel frame in chromed ACC or black painted AN steel thickness 10 mm. , \varnothing 770 mm. with 4 glides. Steel column \varnothing 50x2 mm. with fixed welded plate thickness 5 mm. (fixed height)



**Swivel or fixed
stainless steel base**

- round chromed fixed or swivel base in stainless steel \varnothing 580 mm (fixed height)

Dimensions:

