

KING



Executive armchair with high back and headrest or low back and visitor version.

Seat and back: internal frame in steel with padding in expanded fireproof polyurethane cold injected density min. 60 Kg/m³

Arms:



- **flexible arms** : in flexible steel with upper-injection in integral expanded polyurethane with juncture in die-cast polished aluminium
- fixed aluminium arms: **in die-cast polished aluminium, padded and upholstered on the top**

Seat height adjustment: through gas-spring, cone Ø 28 mm.

Actions:

Fixed plate: (for version without mechanism) in painted steel thickness 2.5 mm., cone Ø 28 mm.

Only on request: Gas system with automatic return of the chair only for 5-star bases with glides and AL4 base (for versions without mechanism)

Tilting mechanism : structure in steel and aluminum with the following adjustments:

- Lever for seat height adjustment and tilting movement control lockable in 5 positions
- anti-shock system
- knob for tension adjustment



-“Knee-tilt” mechanism: steel frame with tilting on decentralized axe, with the following adjustments:

- lever for seat height adjustment
- Lever for tilting movement control, lockable in 5 positions
- Antishock system
- Tilting tension adjustment



Swivel bases and castors:



APN 5 star base with steel inner frame 25x30 mm th.2 mm Ø 670 mm, cover in black polypropylene. (Ansi-Bifma X5.1-1993/8)



AL7 5-star base in die-cast polished aluminum Ø 650 mm



for **APN** and **AL7**: self-braking soft castors Ø 50 mm



APS 5-star base in black reinforced nylon Ø 660 mm



AL6 5-star base in die-cast polished aluminum Ø 654 mm.



for **APS**, **APG**, **APW**, **AL6**, **ANN** and **AL9**: self-braking soft castors Ø 65 mm



APG 5-star base in grey nylon Ø 675 mm



APW 5-star base in white nylon Ø 675 mm



AL9 5-star base in die-cast aluminum, aluminium grey painted Ø 650 mm



ANN 5-star base in die cast aluminium black painted Ø 654 mm



AL3 5-star base in die-cast polished aluminum Ø 654 mm with **chromed gaslift**



AL5 5-star base in die-cast polished aluminum Ø 654 mm with **chromed gaslift**



for **AL3** and **AL5** self-braking soft castors Ø 65 mm **CHROMED**



AWW 5 star base in die cast aluminium white painted Ø 654 mm, with **WHITE GASLIFT**.



for **AWW**: self-braking soft castors Ø 65 mm **WHITE**



AL4 (not for tilting versions) 4-star base in die-cast aluminum Ø 730 mm. with **chromed feet** and **chromed gas-lift**

Fixed frames: sled frame with arms and black polyurethane top, in steel tube Ø 25 mm., black painted (AN), aluminium grey painted (AV) or chromed (AC).

PRODUCT IN ACCORDANCE WITH EUROPEAN STANDARDS EN 1335 – TYPE B

Dimensions:

