

## KONTAT



Complete range of managerial, operative and visitor chairs with backrest in mesh or fully upholstered.

### Versions:

- Padded seat, mesh backrest
- Padded seat and backrest

**Seat:** inner shell in reinforced nylon,  
**filler in cold injected expanded polyurethane D. 65 kg /m3**  
 with black under seat shell

**Backrest:** frame in steel and black polyurethane upholstered with:

- **double polyester mesh**, various colors 
- **all upholsteries available in the fabric card** (fabrics, imitation leather, leather)

**Backrest connection:** in steel with upper injection in black expanded polyurethane and chromed steel insert

### Arms:



- black fixed arms: **in steel with upper injection in black expanded polyurethane**



- chromed fixed arms: **in steel tube with black polyurethane top**

### PU Pad



- **3D** in black nylon with upper part in black soft polyurethane **adjustable in height** for 7,5 cm with 7 locking positions, **rotating and stretchable** for 5 cm



- **4D Adjustable, extensible, rotating and stretchable:** armrests in chromed steel with cover in polypropylene, adjustable in height 100 mm. in 8 positions, extensible 70 mm in 9 positions, rotating from - 30° inner side till +30° outside, stretchable 40 mm


**Seat height adjustment:** gaslift, cone  $\varnothing$  28 mm.

Mechanisms:

fixed plate (fixed backrest): **in black painted steel thickness 2.5 mm., cone  $\varnothing$ 28 mm.**

**Or steel frame SYNCRON mechanism. Adjustments:**

- button for synchron movement control
- lever to adjust the seat height
- 5 locking positions with automatic search (or free floating)
- anti shock system for the backrest
- tension tilting adjustment



**Or steel frame SYNCRON mechanism with sliding system and attitude variator. Adjustments:**

- button for synchron movement control
- lever to adjust the seat height
- 5 locking positions with autom. search (or free floating)
- anti shock system for the backrest
- tension tilting adjustment
- seat sliding system in 5 positions, adjustable in depth for 5 cm.
- attitude variator



**Only on request: Gas system endowed with auto-return action that allows the return of the chair at the start position, only for 5-star bases with glides and AL4 base (for versions without mechanism).**

**Swivel bases and castors:**



**APN** 5 star base with steel inner frame 25x30 mm th.2 mm  $\varnothing$  670 mm, cover in black polypropylene. (Ansi-Bifma X5.1-1993/8)



**AL7** 5-star base in die-cast polished aluminum  $\varnothing$  650 mm



for **APN** and **AL7**: self-braking soft castors  $\varnothing$  50 mm



**APS** 5-star base in black reinforced nylon  $\varnothing$  660 mm



**AL6** 5-star base in die-cast polished aluminum  $\varnothing$  654 mm.



for **APS**, **APG**, **APW**, **AL6**, **ANN** and **AL9**: self-braking soft castors  $\varnothing$  65 mm



**APG** 5-star base in grey nylon  $\varnothing$  675 mm



**APW** 5-star base in white nylon  $\varnothing$  675 mm



**AL9** 5-star base in die-cast aluminum, aluminium grey painted  $\varnothing$  650 mm



**ANN** 5-star base in die cast aluminium black painted  $\varnothing$  654 mm



**AL3** 5-star base in die-cast polished aluminum Ø 654 mm with **chromed gaslift**



**AL5** 5-star base in die-cast polished aluminum Ø 654 mm with **chromed gaslift**



for **AL3** and **AL5** self-braking soft castors Ø 65 mm **CHROMED**



**AWW** 5 star base in die cast aluminium white painted Ø 654 mm, with **WHITE GASLIFT**.



for **AWW**: self-braking soft castors Ø 65 mm **WHITE**



**AL4** (not for tilting versions) 4-star base in die-cast aluminum Ø 730 mm. with chromed feet and **chromed gas-lift**

**Sled frame:** in steel tube **black painted (AN)**, **aluminum painted (AV)** or **chromed (AC)** Ø 25 mm. with top arms in black polyurethane

**Certificates:** (on request for version with mechanism) **European standard EN1335 – Type B**

### Dimensions:

