

## KONVERT



### **Operative and managerial chair:**

- Low back
- High back
- High back with adjustable, padded and upholstered headrest

### **Seat and back:**

- Beech-plywood multi-layer shell
  - Seat thickness 13,5 mm
  - Back thickness 12,0 mm
- Padding in expanded cold-injected polyurethane minimum density 60Kg/m<sup>3</sup>; thickness from 4 to 6 cm

**Back support:** in aluminium grey painted steel with black polypropylene cover

**Headrest:** in steel with cover in expanded polyurethane, padded and upholstered, adjustable

### **Armrests:**

- **fixed:** in steel with upper-injection of black expanded polyurethane
- **fixed:** in die-cast polished aluminum padded and upholstered on the top. Upper-injection of black expanded polyurethane.
- **4d:** **adjustable, extensible, rotating and stretchable armrests:** in chromed steel with cover in polypropylene, adjustable 100 mm in height through Step by Step system in 8 positions, 70 mm extensible in 9 positions, rotating from - 30° inner-side till +30° outside, 40 mm stretchable.

**Seat height adjustment:** gas piston, cone 28.

### **Actions:**

**Fixed plate:** (fixed backrest) in painted steel thickness. 2.5 mm, cone  $\varnothing$  28 mm.

**Only on request:** Gas system endowed with auto-return action that allows the return of the chair at the start position, only for 5-star bases with glides and AL4 base (for versions without mechanism).


**SYNCHRON mechanism:** steel frame with the following adjustments:

- button for synchron movement control
- lever to adjust the seat height
- 5 locking positions with automatic search (or free floating)
- anti shock system for the backrest
- tilting tension adjustment



**SYNCHRON with SLIDE SYSTEM:** steel frame:

- button for synchron movement control
- lever to adjust the seat height
- 5 locking positions with automatic search (or free floating)
- anti shock system for the backrest
- tilting tension adjustment
- slide system for 5 cm depth adjustment with 5 locking positions



**Swivel bases and castors:**



**APN** 5 star base with steel inner frame 25x30 mm th.2 mm Ø 670 mm, cover in black polypropylene. (Ansi-Bifma X5.1-1993/8)



**AL7** 5-star base in die-cast polished aluminum Ø 650 mm



for **APN** and **AL7**: self-braking soft castors Ø 50 mm



**APS** 5-star base in black reinforced nylon Ø 660 mm



**AL6** 5-star base in die-cast polished aluminum Ø 654 mm.



for **APS**, **APG**, **APW**, **AL6**, **ANN** and **AL9**: self-braking soft castors Ø 65 mm



**APG** 5-star base in grey nylon Ø 675 mm



**APW** 5-star base in white nylon Ø 675 mm



**AL9** 5-star base in die-cast aluminum, aluminium grey painted Ø 650 mm



**ANN** 5-star base in die cast aluminium black painted Ø 654 mm



**AL3** 5-star base in die-cast polished aluminum Ø 654 mm with **chromed gaslift**



**AL5** 5-star base in die-cast polished aluminum Ø 654 mm with **chromed gaslift**



for **AL3** and **AL5** self-braking soft castors Ø 65 mm **CHROMED**



**AWW** 5 star base in die cast aluminium white painted Ø 654 mm, with **WHITE GASLIFT**.



for **AWW**: self-braking soft castors Ø 65 mm **WHITE**



**AL4 (not for tilting versions)**  
4-star base in die-cast aluminum Ø 730 mm. with chromed feet and **chromed gas-lift**

**Fixed cantilever frame:**

in steel tube  $\varnothing$  25 mm. sp. 2 mm, cone-shaped, with special aluminium grey +transparent painting **(AV)**, or in chromed steel **(AC)**.

**Certifications:**

**EUROPEAN STANDARDS EN1335 – type “A”** (on request, for versions with mechanism and lumbar support)

**Dimensions:**

