


TECHNICAL SPECIFICATION FORM OF THE PRODUCT (ANNEX-4)							
History		Sequence No.					142
OKAS CODE	39	1	1	3	4	0	0
DMO CATALOG CODE NO							
NAME OF THE PRODUCT	Study Chair						
ORIGINAL PRODUCT CODE (P/N)	FELIX 100 C						
PRODUCT BRAND / MODEL	Goldsit/FELIX						
							
TECHNICAL SPECIFICATIONS							
STUDY CHAIR							
Foot Structure	STAR FOOT						
Width (mm)	680						
Depth (mm)	620						
Height (mm)	1100						
Backrest Upholstery Material	FAUX LEATHER / FABRIC						
Foot Material	ALUMINUM INJECTION						
Armrest Material	POLISHED ALUMINUM						
Other Features	SILENT FLOOR WHEEL IS USED ON STAR FEET.						
For Technical Drawing/Drawing							
Company official name signature and							
DESCRIPTIONS							
Annex-4 Technical Specification Forms for the Product shall be filled in accordance with the "General Rules" in the "List of							



FELIX 100 C WORK CHAIR



yan görünüş



üst görünüş



arka görünüş

Seating Depth	: 450mm
Seating Surface Width	: 490mm
Height of Back Upper Edge from Seating Surface	: 620mm
Back Width	: 490mm
Star Foot Diameter	: 700mm
Width	: 680mm
Depth	: 620mm
Height	: 1100mm

BACK min. ON 11+6 mm FORMED BEEK PLYWOOD Min. 45 Kg/m³ BULK SPONGE IS USED.

BACKGROUND WITH ITS MECHANISMS, SEATS AND BACKS THAT CAN MOVE SIMULTANEOUSLY ABOUT AN AXIS OR CAN MAKE BACK ANGLE ADJUSTMENT (SYNCHRONIZED), AGAINST ANY DEGREE OF ITS BACK ATTITUDE, SEATING LOCATION AND BUTHOUSE APPLICATION CANNOT BE ABLE TO MAKE A POOLITY ENERGY, BAYTONIZENY APARTMENT 3, A POOLITYA ENERGY APARTMENT, A POOLETY, APPROACH, BAYATHENS. SYNCHRONIC

FIVE STAR FORM POLISHED, OCTOPUS ALUMINUM FOOT. SHOCK ABSORBER HUB FEDER SUPPORT 1.700 Kg ±50 g. .WHEELS ARE Ø11 mm WITH RING PIN, 50mm Ø DOUBLE, MADE OF PLASTIC MATERIAL IMPORTED FROM TAIWAN.SILENT WHEEL IS USED.

Fabric at least 90% Polyester, at least 210 gr/m² / Artificial leather at least 10% polyurethane, 70% PVC, at least 315 gr/m²/File 350 gr/m²

ALUMINUM BODY ON PLASTIC FLOOR PAD, FIXED ARM WITH NO DOWN UP MOVEMENT.

MADE SPECIALLY TO THE MODEL, IN ALUMINUM MOLDS WITH PNC CONTROLLED HIGH PRESSURE MACHINES Min. 45 Kg/m³ BULK FOAM WITHOUT METAL CONSTRUCTION IS USED.

SEAT min. ON 11 mm FORMED BEEK PLYWOOD Min. 45 Kg/m³ BULK SPONGE IS USED.

IMPORTED KLAS 4 SHOCK ABSORBER IS USED THAT CAN TURN IN 360° ON ITS AXIS.

