


TECHNICAL SPECIFICATION FORM OF THE PRODUCT (ANNEX-4)							
History	Sequence No.						121
OKAS CODE	39	1	1	3	4	0	0
DMO CATALOG CODE NO							
NAME OF THE PRODUCT	Study Chair						
ORIGINAL PRODUCT CODE (P/N)	MERCURY 100 C						
PRODUCT BRAND / MODEL	Goldsit/MERKUR						
							
TECHNICAL SPECIFICATIONS							
STUDY CHAIR							
Foot Structure	STAR FOOT						
Width (mm)	595						
Depth (mm)	580						
Height (mm)	990						
Backrest Upholstery Material	NET FABRIC						
Foot Material	ALUMINUM INJECTION						
Armrest Material	POLISHED ALUMINUM						
Other Features	USES SILENT HARD FLOOR WHEEL.						
For Technical Drawing/Drawing							
Company official name signature and							
DESCRIPTIONS							
Annex-4 Technical Specification Forms for the Product shall be filled in accordance with the "General Rules" in the "List of							



MERKÜR 100 C WORK CHAIR



ön görünüş



yan görünüş



üst görünüş



arka görünüş

Seating Depth	: 420-470 mm
Seating Surface Width	: 500mm
Height of Back Upper Edge from Seating Surface	: 750mm
Back Width	: 450mm
Star Foot Diameter	: 700mm
Width	: 595mm
Depth	: 580mm
Height	: 990mm

THE BACK IS PLASTIC AND WITH MESH. IT HAS PLASTIC MOVABLE WAIST SUPPORT.

BACK SEAT AND BACK SEAT AGAINST ANY DEGREE OF ITS BACK ATTITUDE, CAN MAKE A SEAT AGAINST ANY DEGREE OF ITS BACK ATTITUDE, CAN BE MADE AT THE POOL AND BREAK, APPROACH, APPROPRIATE, BREAKTHE, BREAKEN, BREAKEN, BREAK, BREAKEN, BREAK, APARTMENT AND TAIL SYNCHRONIC MECHANISM WITH SPRING PRESSURE ADJUSTMENT ACCORDING TO INDIVIDUAL WEIGHTS.

FIVE STAR FORM POLISHED, OCTOPUS ALUMINUM FOOT. SHOCK ABSORBER HUB FEDER SUPPORT 1.700 Kg $\pm$ 50 g. .WHEELS ARE $\varnothing$ 11 mm WITH RING PIN, 50mm $\varnothing$ DOUBLE, MADE OF PLASTIC MATERIAL IMPORTED FROM TAIWAN.SILENT WHEEL IS USED.

METAL PARTS MIN. 40 micron THICKNESS, ELECTROSTATIC PAINTED AND POLISHED.

Fabric at least 90% Polyester, at least 210 gr/m² / Artificial leather at least 10% polyurethane, 70% PVC, at least 315 gr/m²/File 350 gr/m²

ALUMINUM BODY WITH POLYURETHANE PAD ON, FIXED ARM WITH NO DOWN UP MOVEMENT.

HIGH PRESSURE MACHINES WITH PLC CONTROL IN ALUMINUM MOLDS MADE SPECIALLY TO THE MODEL Min. 45 Kg/m³ BULK FOAM WITHOUT METAL CONSTRUCTION IS USED.

TURAK PP COPOLIMER PLASTIC MATERIAL IS SPECIALLY MANUFACTURED CARRIER PLASTIC ON THE MODEL.

IMPORTED KLAS 4 SHOCK ABSORBER IS USED THAT CAN TURN IN 360° ON ITS AXIS.

