


TECHNICAL SPECIFICATION FORM OF THE PRODUCT (ANNEX-4)							
History		Sequence No.					268
OKAS CODE	39	1	1	3	4	0	0
DMO CATALOG CODE NO							
NAME OF THE PRODUCT	Study Chair						
ORIGINAL PRODUCT CODE (P/N)	MERCURY 100 PA						
PRODUCT BRAND / MODEL	Goldsit/MERKUR						
							
TECHNICAL SPECIFICATIONS							
STUDY CHAIR							
Foot Structure	STAR FOOT						
Width (mm)	610-650						
Depth (mm)	580						
Height (mm)	1000						
Backrest Upholstery Material	NET FABRIC						
Foot Material	BLACK POLYPROPYLENE						
Armrest Material	BLACK POLYPROPYLENE						
Other Features	USES SILENT HARD FLOOR WHEEL.						
For Technical Drawing/Drawing							
Company official name signature and							
DESCRIPTIONS							
Annex-4 Technical Specification Forms for the Product shall be filled in accordance with the "General Rules" in the "List of							



MERKÜR 100 PA WORK CHAIR



ön görünüş



yan görünüş



üst görünüş



arka görünüş

Seating Depth	: 420-470 mm
Seating Surface Width	: 500mm
Height of Back Upper Edge from Seating Surface	: 550mm
Back Width	: 460mm
Star Foot Diameter	: 700mm
Width	: 610-650 mm
Depth	: 580mm
Height	: 1000mm

THE BACK IS PLASTIC AND WITH MESH. IT HAS PLASTIC MOVABLE WAIST SUPPORT.

BACK SEAT AND BACK SEAT AGAINST ANY DEGREE OF ITS BACK ATTITUDE, CAN MAKE A SEAT AGAINST ANY DEGREE OF ITS BACK ATTITUDE, CAN BE MADE AT THE POOL AND BREAK, APPROACH, APPROPRIATE, BREAKTHE, BREAKEN, BREAKEN, BREAK, BREAKEN, BREAK, APARTMENT AND TAIL SYNCHRONIC MECHANISM WITH SPRING PRESSURE ADJUSTMENT ACCORDING TO INDIVIDUAL WEIGHTS.

FIVE STAR FORM NYLON 6 30% GLASS FIBER SHOCK ABSORBER HUB WITH ZAMAK BRACE SUPPORTED 1,600 Kg $\pm$ 50 g OCTOPUS FOOT.WHEELS $\varnothing$ 11 mm WITH SECOND PIN, 50mm $\varnothing$ DUBLE DUBLERE DUPLATILE MALLERZE.

METAL PARTS MIN. 40 micron THICKNESS, ELECTROSTATIC PAINTED.

Fabric at least 90% Polyester, at least 210 gr/m² / Artificial leather at least 10% polyurethane, 70% PVC, at least 315 gr/m²/File 350 gr/m²

PP COPOLIMER AND PA 6 30% GLASS FIBER PLASTIC MATERIAL WITH ADJUSTABLE HEIGHT, ARMO PLASTIC MATERIAL (INTERIOR PLASTIC FRAME AND FOAM) AND HORIZONTAL RIGHT-LEFT AND EKEKEN KEREKEYOL EAKEN-LEFT VEAKABLE.

HIGH PRESSURE MACHINES WITH PLC CONTROL IN ALUMINUM MOLDS MADE SPECIALLY TO THE MODEL Min. 45 Kg/m³ BULK FOAM WITHOUT METAL CONSTRUCTION IS USED.

TURAK PP COPOLIMER PLASTIC MATERIAL IS SPECIALLY MANUFACTURED CARRIER PLASTIC ON THE MODEL.

IMPORTED KLAS 4 SHOCK ABSORBER IS USED THAT CAN TURN IN 360° ON ITS AXIS.