


QUATRO 000 PA STUDY CHAIR



ön görünüş



yan görünüş



üst görünüş



arka görünüş

Seating Depth	: 450mm
Seating Surface Width	: 500mm
Height of Back Upper Edge from Seating Surface	: 740mm
Back Width	: 480mm
Star Foot Diameter	: 700mm
Width	: 610mm
Depth	: 620mm
Height	: 1190mm

IT HAS ADJUSTABLE HEIGHT AND MOVING HEAD ON SINGLE AXIS. HEAD CARRIER IS ALUMINUM, INTERIOR AND EXTERNAL PP COPOLYMER PLASTIC MATERIAL ON THE MODEL, SPECIALLY MACHINED, PRESSED ALUMINUM MINIMUM MOLDS (PLC MOLD) 45 Kg/m³ BULK SPONGE IS USED. IT IS FLOOR.

THE BACK IS PLASTIC AND WITH MESH. THERE ARE FEDERS THAT PREVENT DEFORMATION OF THE BACK PLASTIC'S TENSION OVER TIME. PLASTIC HAS FIXED WAIST SUPPORT.

MECHANISM SEAT AND BACK MOVING SIMULTANEOUSLY ABOUT AN AXIS. LOCKING IN AT LEAST 3 POSITIONS, (SYNCHRONIZED) BACK TILT TILT MECHANISM.

FIVE STAR FORM NYLON 6 30% GLASS FIBER SHOCK ABSORBER HUB WITH ZAMAK BRACKET SUPPORTED WITH 1,600 Kg ±50 g OCTOPUS FOOT. WHEELS Ø11 mm WITH RING PIN, 50mm Ø DOUBLE, PLASTIC MATERIALS, DENTAL MATERIALS. USES SILENT WHEEL.

METAL PARTS MIN. 40 micron THICKNESS, ELECTROSTATIC PAINTED.

Fabric at least 90% Polyester, at least 210 gr/m² / Artificial leather at least 10% polyurethane, 70% PVC, at least 315 gr/m²/File 350 gr/m²

PP COPOLYMER PLASTIC MATERIAL, HEIGHT ADJUSTABLE, ARMRESTS WITH POLYURETHANE MATERIAL (INTERIOR WITH PLASTIC FRAME).

MADE SPECIALLY TO THE MODEL, IN ALUMINUM MOLDS WITH PNC CONTROLLED HIGH PRESSURE MACHINES Min. 45 Kg/m³ BULK FOAM WITHOUT METAL CONSTRUCTION IS USED.

SEAT MIN. IT CONSISTS OF BEEKEEN PAPE FORM FORM WITH 11 mm THICKNESS. THE BOTTOM OF THE SEAT HAS A PP MATERIAL PLASTIC COVER.

IMPORTED CLASS 4 SHOCK ABSORBER IS USED THAT CAN TURN IN 360° ON ITS AXIS.

