


TECHNICAL SPECIFICATION FORM OF THE PRODUCT (ANNEX-4)							
History	Sequence No.						291
OKAS CODE	39	1	1	3	4	0	0
DMO CATALOG CODE NO							
NAME OF THE PRODUCT	Study Chair						
ORIGINAL PRODUCT CODE (P/N)	QUATRO 100 CA						
PRODUCT BRAND / MODEL	Goldsit/QUATRO						
							
TECHNICAL SPECIFICATIONS							
STUDY CHAIR							
Foot Structure	STAR FOOT						
Width (mm)	610						
Depth (mm)	600						
Height (mm)	990						
Backrest Upholstery Material	NET FABRIC						
Foot Material	ALUMINUM INJECTION						
Armrest Material	METAL AND BLACK POLYPROPYLENE						
Other Features	USES SILENT HARD FLOOR WHEEL.						
For Technical Drawing/Drawing							
Company official name signature and							
DESCRIPTIONS							
Annex-4 Technical Specification Forms for the Product shall be filled in accordance with the "General Rules" in the "List of							




QUATRO 100 CA STUDY CHAIR



ön görünüş



yan görünüş



üst görünüş




arka görünüş

Seating Depth	: 450mm
Seating Surface Width	: 500mm
Height of Back Upper Edge from Seating Surface	: 550mm
Back Width	: 480mm
Star Foot Diameter	: 700mm
Width	: 610mm
Depth	: 600mm
Height	: 990mm

THE BACK IS PLASTIC AND WITH MESH. THERE ARE FEDERS THAT PREVENT DEFORMATION OF THE BACK PLASTIC'S TENSION OVER TIME. PLASTIC HAS FIXED WAIST SUPPORT.

MECHANISM SEAT AND BACK MOVING SIMULTANEOUSLY ABOUT AN AXIS. LOCKING IN AT LEAST 3 POSITIONS, (SYNCHRONIZED) BACK TILT TILT MECHANISM.

FIVE STAR FORM POLISHED, OCTOPUS ALUMINUM FOOT. SHOCK ABSORBER HUB FEDER SUPPORT 1.700 Kg $\pm$ 50 g. .WHEELS ARE $\varnothing$ 11 mm WITH RING PIN, 50mm $\varnothing$ DOUBLE, MADE OF PLASTIC MATERIAL IMPORTED FROM TAIWAN.SILENT WHEEL IS USED.




Fabric at least 90% Polyester, at least 210 gr/m² / Artificial leather at least 10% polyurethane, 70% PVC, at least 315 gr/m²/File 350 gr/m²

PP COPOLIMER PLASTIC AND METAL OVAL PIPE MATERIAL NICKELATED HEIGHT ADJUSTABLE, ARMRESTS WITH POLYURETHANE (INTERIOR PLASTIC FRAME).

MADE SPECIALLY TO THE MODEL, IN ALUMINUM MOLDS WITH PNC CONTROLLED HIGH PRESSURE MACHINES Min. 45 Kg/m³ BULK FOAM WITHOUT METAL CONSTRUCTION IS USED.

SEAT MIN. IT CONSISTS OF BEEKEEN PAPE FORM FORM WITH 11 mm THICKNESS. THE BOTTOM OF THE SEAT HAS A PP MATERIAL PLASTIC COVER.

IMPORTED KLASS 4 SHOCK ABSORBER IS USED THAT CAN TURN IN 360° ON ITS AXIS.



METAL PARTS MIN. 40 micron THICKNESS, ELECTROSTATIC PAINTED AND POLISHED.