

TECHNICAL SPECIFICATION FORM OF THE PRODUCT (ANNEX-4)

History		Sequence No.					297
OKAS CODE	39	1	1	3	4	0	0

DMO CATALOG CODE NO	
NAME OF THE PRODUCT	Study Chair
ORIGINAL PRODUCT CODE (P/N)	SANDAX 100PA
PRODUCT BRAND / MODEL	Goldsit/SANDAX



TECHNICAL SPECIFICATIONS

STUDY CHAIR

Foot Structure	STAR FOOT
Width (mm)	610
Depth (mm)	620
Height (mm)	1030
Backrest Upholstery Material	NET FABRIC
Foot Material	BLACK POLYPROPYLENE
Armrest Material	BLACK POLYPROPYLENE
Other Features	P6 30% FIBER GLASS MATERIAL AND SILENT HARD FLOOR WHEEL IS USED ON PLASTIC FEET.

For Technical Drawing/Drawing	
Company official name signature and	

DESCRIPTIONS

Annex-4 Technical Specification Forms for the Product shall be filled in accordance with the "General Rules" in the "List of



SANDAX 100 PA STUDY CHAIR



ön görünüş



yan görünüş



üst görünüş



arka görünüş

- Seating Depth	: 450mm
- Seating Surface Width	: 500mm
- Height of Upper Back Edge from Seating Surface	: 580mm
- Back Width	: 470mm
- Star Foot Diameter	: 700mm
Width	: 610mm
Depth	: 620mm
Height	: 1030mm

THE BACK IS PLASTIC AND WITH MESH. IT HAS PLASTIC MOVABLE WAIST SUPPORT.

BACKGROUND WITH ITS MECHANISMS, SEATS AND BACKS THAT CAN MOVE SIMULTANEOUSLY ABOUT AN AXIS OR CAN MAKE BACK ANGLE ADJUSTMENT (SYNCHRONIZED), AGAINST ANY DEGREE OF ITS BACK ATTITUDE, SEATING LOCATION AND BUTHOUSE APPLICATION CANNOT BE ABLE TO MAKE A POOLITY ENERGY, BAYTONIZENY APARTMENT 3, A POOLITYA ENERGY APARTMENT, A POOLETY, APPROACH, BAYATHENS. SYNCHRONIC MECHANISM WITH SPRING PRESSURE

FIVE STAR FORM NYLON 6 30% GLASS FIBER SHOCK ABSORBER HUB WITH ZAMAK BRACE SUPPORTED 1,600 Kg \pm 50 g OCTOPUS FOOT.WHEELS ϕ 11 mm WITH SECOND PIN, 50mm ϕ DUBLE DUBLERE DUPLATILE MALLERZE.

METAL PARTS ARE ELECTROSTATIC PAINTED AND min. IT IS 40 microns thick.

Fabric at least 90% Polyester, at least 210 gr/m² / Artificial leather at least 10% polyurethane, 70% PVC, at least 315 gr/m²/File 350 gr/m²

PP COPOLIMER PLASTIC MATERIAL, HEIGHT ADJUSTABLE, ARMRESTS WITH POLYURETHANE MATERIAL (INTERIOR WITH PLASTIC FRAME).

HIGH PRESSURE MACHINES WITH PLC CONTROL IN ALUMINUM MOLDS MADE SPECIALLY TO THE MODEL Min. 45 Kg/m³ BULK FOAM WITHOUT METAL CONSTRUCTION IS USED.

SEAT MIN. IT CONSISTS OF BEEKEN PAPE FORM FORM WITH 11 mm THICKNESS. THE BOTTOM OF THE SEAT HAS A PP MATERIAL PLASTIC COVER.

IMPORTED CLASS 4 SHOCK ABSORBER IS USED THAT CAN TURN IN 360° ON ITS AXIS.