

VENUS 000 GC STUDY CHAIR



ön görünüş



yan görünüş



üst görünüş



arka görünüş

Seating Depth	: 450-500mm
Seating Surface Width	: 500mm
Height of Back Upper Edge from Seating Surface	: 740mm
Back Width	: 440mm
Star Foot Diameter	: 700mm
Width	: 595mm
Depth	: 590mm
Height	: 1210mm

IT HAS AN ADJUSTABLE HEIGHT, MOVING HEAD ON SINGLE AXIS. THE HEAD CARRIER IS PLASTIC MATERIAL, SPECIALLY MANUFACTURED ON THE MODEL, WITH CASTING SPONGE AND FLOOR.

THE INSIDE OF THE BACK IS BLACK PLASTIC AND IT IS FLOORED BY ADHESIVE WITH UNCONSTRUCTIONAL BULK SPONGE. THERE IS COLOR PLASTIC ON THE OUTER OF THE BACK. IT HAS PLASTIC MOVABLE WAIST SUPPORT.

A SEAT AND BACK BACK, SYNCHRONIZED, CAN MAKE SEAT AND BACK SYNCHRONOUS AGAINST AN AXIS, OR CAN MAKE A SEAT AGAINST ANY DEGREE OF ITS BACK LOTS AND TAIL SYNCHRONIC MECHANISM WITH SPRING PRESSURE ADJUSTMENT ACCORDING TO INDIVIDUAL WEIGHTS.

FIVE STAR FORM POLISHED, OCTOPUS ALUMINUM FOOT. SHOCK ABSORBER HUB FEDER SUPPORT 1.700 Kg \pm 50 g. .WHEELS ARE \varnothing 11 mm WITH RING PIN, 50mm \varnothing DOUBLE, MADE OF PLASTIC MATERIAL IMPORTED FROM TAIWAN.SILENT WHEEL IS USED.

Fabric at least 90% Polyester, at least 210 gr/m² / Artificial leather at least 10% polyurethane, 70% PVC, at least 315 gr/m²/File 350 gr/m²

ALUMINUM BODY WITH POLYURETHANE PAD ON, FIXED ARM WITH NO DOWN UP MOVEMENT.

HIGH PRESSURE MACHINES WITH PLC CONTROL IN ALUMINUM MOLDS MADE SPECIALLY TO THE MODEL Min. 45 Kg/m³ BULK FOAM WITHOUT METAL CONSTRUCTION IS USED.

TURAK PP COPOLIMER PLASTIC MATERIAL IS SPECIALLY MANUFACTURED CARRIER PLASTIC ON THE MODEL.

IMPORTED KLAS 4 SHOCK ABSORBER IS USED THAT CAN TURN IN 360° ON ITS AXIS.